

Features

-Compatible with 200lb (120l), 400lb (200L) and 600lb (400L) dump buggies. -The tipping height is adjustable.

Tip height 'without' a chute fitted:
Tip height adjustable range for 400lb bins is – 55 to 90" (in 4" increments)
Tip height adjustable range for 600lb bins is – 47 to 82.7" (in 4" increments)

Tip height with a chute fitted:
Tip height adjustable range for 400lb bins is – 47 – 82.7" (in 4" increments)
Tip height adjustable range for 600lb bins is – 47 to 82.7" (in 4" increments)

-The machine is mobile as standard, with fixing brackets provided to fix the column dumper into position if required.

-304 stainless steel

-Welded construction throughout

-Motor gearbox driven

-Chute fitted as standard



ISCA - Column Dumper

Technical Specifications

-Controls/orientation – Hold to run push buttons / Right-hand side
-Stainless steel – Grade 304
-Lifting capacity – 660 lbs
-Max tipping height (adjustable) – See description above
-Tipping reach – Customized to your application with a chute if required
-Tipping angle – 135 degrees (45 degrees from horizontal)
-Overall machine height – 127.5"
-Container suitability – Dump buggy 200, 400 + 600lb (or similar container)
-Base – Mobile base (with fixing brackets on base frame)
-Mains supply as std – 480v 3PH 60Hz – Grounded (can be switched to 240v on site)
-Control circuit – 24V AC
-Electrical rating – IP65
-Drive Type – Braked motor gearbox + roller chain (simplex 3/4" chain)
-Lift speed – 21 ft/min
-Approx net machine weight – 660 Lb

Customized options available

- Guarding and Fixed base

-We have 'off the shelf' machines, that can be further customized, or we can create a new solution for your specific needs.





